

MSG 20

Compact seats with mechanical suspension





TECHNICAL DATA MSG 20

All MSG 20 seats are optimally designed to attenuate the vibrations to which forklift operators are typically subjected, featuring suspension travel of 60 mm. They are also simple to set to any user weight between 50 and 130 kg. In addition, the seat's fore-aft position can be varied by up to 150 mm to provide enough space for every body size and work situation.





Features • Standard O Optional

| | MSG20 | MSG20 | MSG20 | MSG20 | MSG20 |
|---------------------------------|--------|--------|---------|--------|---------|
| Article no. fabric | | | 1293150 | | |
| Article no. imitation leather | 134015 | 141999 | 141001 | 143465 | 1017487 |
| Suspension mechanical | • | • | • | • | • |
| Suspension stroke 60 mm | • | • | | • | • |
| ① Weight adjustment 50 - 130 kg | • | • | • | • | • |
| 2 Fore/aft adjustment | | | | | |
| 150 mm | | • | • | • | |
| 210 mm | • | | | | • |
| 3 Adjustable backrest angle | • | • | • | • | • |
| 4 Restraint system | | | | | |
| Duo-sensitive retractable belt | | | | • | |
| Belt holder preassembled | • | | | | • |
| Seat cushion width | 470 mm | 470 mm | 470 mm | 470 mm | 470 mm |
| Operator presence switch (OPS) | | | • | • | • |
| OPTIONAL FEATURES | | | | | |
| 5 Armrests foldable 54 x 300 mm | 0 | 0 | 0 | 0 | 0 |
| 6 Document box | 0 | 0 | 0 | 0 | 0 |
| Duo-sensitive retractable belt | | 0 | 0 | | |
| Retractor belt | 0 | 0 | 0 | | 0 |
| Static belt | 0 | 0 | 0 | | 0 |
| Seat heating | 0 | 0 | 0 | 0 | 0 |

Measurements (installation dimensions)

